

Replacement Controller

Model numbers: TF-CONT180B

Features & Benefits

- 1.8Bar cut in pressure
- Loss of prime protection
- 2 year replacement warranty
- Totalflo Controller to suit:
TF40J, TF50J, TF117MS, TF40J-18, TF50J-18, TF117MS-18*



Applications

- Household water supply
- Replacement controllers specifically ranged to support Totalflo HPS systems

ELECTRICAL DATA & OPERATING LIMITS

Voltage / Frequency	220 – 240V ~ 50 – 60Hz
Phase	Single
Insulation	Double
Ingress protection	IP67
Cut in Pressure	1.8Bar (180kPa)
Inlet/outlet	1" (25mm BSP male)
Max compatible pump kW	1.1kW (do not connect to HPS over 1.1kW)
Max current	10A
Max. working pressure	1 mPa (10bar)
Max recommended operating temp	50°C
Max recommended ambient temp	60°C
Powerlead type	3 x 0.75mm ² (C38) with 3-pin plug
Powerlead length	1.95m controller to plug 550mm controller to pump capacitor box
Installation	Electrical powerlead from controller into the pump should only be installed by licensed electrical worker
Packaging	Single controller in white carton with label, (12pc per master outer carton)

*also suitable for SJ35-04, SJ35-04PC, SJ60-08, SJ60-08PC



Tested in compliance with
AS/NZS 4020
for use in contact with safe drinking water

This product holds a 2 Year Replacement Guarantee due to manufacturing defect with no serviceable spare parts or infield service

DWP2184/0621